



robin

La qualité en peinture

Technical data sheet  
Updated : 02/10/2007

## **ACRYTON** *Tint for frontages*

### **COMPOSITION:**

Pliolite resin (acrylic-vinyl) of the Goodyear company.

### **CHARACTERISTICS:**

ACRYTON exactly matches the technical requirements of the Goodyear company, which allows our company to be approved supplier of Goodyear Luxembourg.

### **PROPERTIES:**

ACRYTON applies to new and existing funds, such as plaster, concrete, stones, bricks, wood etc. ...

ACRYTON offers excellent adhesion on porous or powdery surfaces

The ACRYTON based coatings have a very good breathability allowing water to evaporate the carrier without blistering. These coatings are waterproof and resistant to the alkalinity of concrete, dirt, mildew and ultraviolet rays.

### **INSTRUCTIONS:**

On very porous surfaces, is used as filler and catchy Acryton-Tiefengrund, diluted at a rate of 1 part-Acryton Tiefengrund to 1 part white spirit.

On very absorbent surfaces, a primer based paint Acryton diluted 20-25% with White Spirit is suitable.

ACRYTON is to be diluted with white spirit

- For application by brush or brush 5 to 10%
- For spray application 20 to 25%

### **OUTPUT:**

- ± 6 m<sup>2</sup>/ltr with brush and roll
- ± 7 m<sup>2</sup>/ltr with spray gun

**CLEANING:** equipment with white spirit

### **TINTS:**

white, black, any other color on request.

### **DRYING:**

at 20 ° C and 60% relative humidity

Tack free: 1 hour

Resistant to rain: 2 hours

redoublable: 24 hours

#### Peintures ROBIN S.A.

31 rue de la Gare // L-8705 Useldange

T (+352) 23 63 23-1 // F (+352) 23 63 23-58

[peintures@robin.lu](mailto:peintures@robin.lu) // [www.robin.lu](http://www.robin.lu)

7 rue Jean Fischbach - Z.a. am Bann // L-3372 Leudelange

T (+352) 49 31 61-1 // F (+352) 49 31 61-880

[peintures.standex@robin.lu](mailto:peintures.standex@robin.lu) // [www.robin.lu](http://www.robin.lu)



r o b i n

La qualité en peinture

Technical data sheet  
Updated : 02/10/2007

**CONSERVATION:**

1 year in original packaging.  
ACRYTON is incompatible with any other product.

**PACKAGE:**

750 ml – 2,5 ltr – 5 ltr – 10 ltr

**VOC** : EU limit values for this product (cat.IIA / i): 600g / l (2007) - 500g / l (2010)

L'acryton contains 413g/l of VOC

Remarque : Warranty invalid, if other system than provided by ROBIN S.A. is used

*Nota : cancel and replaces the former editions. It's up to our customers to check, before application, if it is indeed the last edition. The information contained in this note has only one indicative range and can not compensate a description suitable with the nature and the state of funds to be treated.*

**Peintures ROBIN S.A.**

31 rue de la Gare // L-8705 Useldange  
T (+352) 23 63 23-1 // F (+352) 23 63 23-58  
[peintures@robin.lu](mailto:peintures@robin.lu) // [www.robin.lu](http://www.robin.lu)

7 rue Jean Fischbach - Z.a. am Bann // L-3372 Leudelange  
T (+352) 49 31 61-1 // F (+352) 49 31 61-880  
[peintures.standex@robin.lu](mailto:peintures.standex@robin.lu) // [www.robin.lu](http://www.robin.lu)