

DEGRAISSEUR HYDRO L-19400

Ready to use, water-based solution

Due to regulations regarding VOC Degreaser L-19400 Hydro has been specially developed as a degreasing agent prior to painting.

CARACTERISTIQUES

- Not affected by the rule (VOC content <15 g / l)
- Faster drying than conventional water-based cleaning agents.
- Good ability to dissolve corrosion protection oils
- For use on steel surfaces, stainless steel, brass, zinc, copper and most alloys of aluminum and anodized brackets
- The surfactants are biodegradable according to EU directives
- Acceptance skin significantly higher compared to cleaners containing solvents
- Can be used safely down to -5 ° C
- Contains corrosion inhibitors to prevent further corrosion of the surfaces in the short term

USAGE / APPLICATION

Dégraissseur Hydro-L 19 400 is applied preferably by spraying / wiping.
Depending on the degree of soiling, we recommend leaving the product to work approx. 30 to 60 seconds before wiping.
When soiling is particularly important, it may be necessary to repeat the cleaning operation.
It is not necessary to rinse the surfaces treated with water.
Direct application of paint.

For further information, please refer to the safety data sheet.

Packaging: 1 ltr Spray - 1 ltr - 5 liters - 25 ltr

Note: This product is no longer guaranteed, since it has been dyed by other systems than ROBIN SA.

Note: cancels and supersedes the previous editions. It belongs to our customers to verify, before any implementation, that it is the last edition. The information in this notice are only indicative range and can not replace a proper description of the nature and state funds to deal.