



robin

La qualité en peinture

Technical datasheet  
Updated : 08/2016

## **GRUNDIERWEISS** White adhesion primer for interior and exterior

**COMPOSITION:** Copolymeric acrylic waterbased resin.

**PROPERTIES AND APPLICATION:**

- White adhesion primer for interior and exterior
- GRUNDIERWEISS is used as a adhesion primer for plaster, concrete, cement, bricks.
- Viscosity : 800cp (haake, 22°C, rotor 1)
- Density: 1,45

**DRYING:** Re-coatable after 4 hours.

**USE:**

- With brush or roll
- Air-mix Application: optimal output with a dilution of 5% of water, using a nozzle 415 to 421 or 515 to 521 and pressures between 120 and 220 bar (395-225V GRACO FinishPro EUR VISION Airless and Air-attended)

**CLEANING:** with water

**COVERAGE:** 10-12 m<sup>2</sup> /Ltr

**COLOUR:** white

**PACKAGING:** 12,5 ltr

**REMARQUE:** Does not stand frost

**VOC** Minimal values in UE for this product (cat.IIA/a) are 75g/l(2007) and 30g/l(2010), current value: 2 g/l

*Nota : cancel and replaces the former editions. It's up to our customers to check, before application, if it is indeed the last edition. The information contained in this note has only one indicative range and can not compensate a description suitable with the nature and the state of funds to be treated.*

**Peintures ROBIN S.A.**

31 rue de la Gare // L-8705 Useldange  
T (+352) 23 63 23-1 // F (+352) 23 63 23-58  
[peintures@robin.lu](mailto:peintures@robin.lu) // [www.robin.lu](http://www.robin.lu)

7 rue Jean Fischbach - Z.a. am Bann // L-3372 Leudelange  
T (+352) 49 31 61-1 // F (+352) 49 31 61-880  
[peintures.standex@robin.lu](mailto:peintures.standex@robin.lu) // [www.robin.lu](http://www.robin.lu)