

HYDROFACER

Mat fuller primer for indoors use

Composition:

Acrylic resin 100% waterbased

Properties and applications:

- Mat fuller primer for indoors use
- HYDROFACER is applied as universal primer on wood, gypsum, plaster, cement, cement asbestos, MDF (Main Distribution Frame), particle board, old alkyd colour
- HYDROFACER isolates tannic, acid and nicotine
- HYDROPRIMER can be used as primer fuller and top coat
- Solids content: 60 %
- Density: 1,47

Drying: paintable after 4 hours

Instructions for use:

1. Layer: dilute with 5 % of water
2. Layer: dilute with 3-4 % of water

Cleaning: with water

Consumption: 8 to 10 m²/ltr

Colour shades: white in stock

Packaging: 0,75 ltr - 2,5 ltr – 12,5 Ltr

Note: protect from frost

VOC : EU limits for this product:(Kat.A/a) : 30g/l(2010) ; Hydrofacer contains 3g/l VOC

Explanatory note: This product will not be guaranteed anymore if it is tinted by other systems than those of ROBIN S.A.

Note: cancels and replaces former editions. It is up to our customers to check, before application, that this is indeed the last edition. The information contained in this note has only one indicative range and cannot compensate a description suitable with the nature and the state of the funds to be treated.

Peintures ROBIN S.A.

31 rue de la Gare // L-8705 Useldange
T (+352) 23 63 23-1 // F (+352) 23 63 23-58
peintures@robin.lu // www.robin.lu

7 rue Jean Fischbach - Z.a. am Bann // L-3372 Leudelange
T (+352) 49 31 61-1 // F (+352) 49 31 61-880
peintures.standex@robin.lu // www.robin.lu