

## **HYDROFIX**

### **COMPOSITION:**

Acrylic resins in aqueous dispersion

### **PROPERTIES:**

Hydrofix is used as a pattern layer on surfaces like concrete, bricks, plaster, cements... inside or outside, before applying a waterbased topcoat such as ROBINCRYL – ROBINCRYL MAT – DISPERSOL – DISPERTEX – CREPI...

Hydrofix is suitable for patterns on existing isolating frontages with polystyrene.

Hydrofix strengthens dead plaster making it harder and easier to sand.

### **INSTRUCTIONS:**

Hydrofix is ready for use. Apply with brush or spraygun.

**CLEANING :** with water

**COVERAGE:** ± 10 m<sup>2</sup> / Liter

**PACKAGING:** 1 Liter – 5 Liters – 10 Liters

*Nota : cancel and replaces the former editions. It's up to our customers to check, before application, if it is indeed the last edition. The information contained in this note has only one indicative range and can not compensate a description suitable with the nature and the state of funds to be treated.*

#### **Peintures ROBIN S.A.**

31 rue de la Gare // L-8705 Useldange  
T (+352) 23 63 23-1 // F (+352) 23 63 23-58  
[peintures@robin.lu](mailto:peintures@robin.lu) // [www.robin.lu](http://www.robin.lu)

7 rue Jean Fischbach - Z.a. am Bann // L-3372 Leudelange  
T (+352) 49 31 61-1 // F (+352) 49 31 61-880  
[peintures.stadox@robin.lu](mailto:peintures.stadox@robin.lu) // [www.robin.lu](http://www.robin.lu)