



R O B I N H Y D[®]

BÂTIMENT

Technical data sheet

HYDROMAT
Matt enamel for interiors

COMPOSITION: 100% Acrylic water dilutable resin

PROPERTIES AND USAGE:

- Hydromat is an enamel for interiors
- HYDROMAT is suitable for wood, plaster, crepis, cement, eternit, MDF, coated plaster boards, plywood, beaverboard, crepis, old alkalyd tints...
- HYDROMAT has blocking properties of nicotine and tannins.
- HYDROMAT can be used as background and finishing, apply very well with a perfect tense and makes an absolutely dull.
- Dry extract: 60 %
- Density: 1,47
- Wet abrasion test according to EN ISO 11998: Class 1
- EN ISO 6504-3 : Classe 2

DRYING: Recovery after 4 hours.

INSTRUCTIONS:

HYDROMAT should be diluted with 5 % of water for the 1st layer. Dilute with 3 – 4 % of water for a 2nd layer and later (finish)

CLEANING: with water

COVERAGE: 8 – 10 m² /ltr

TINT: white and tints ROBIN-MIX Série E1 to E15 (N°1-2-3 and 6-7-8)

PACKAGING: 750 ml – 2,5 Ltr – 12,5 Ltr

REMARQUE: Keep away from frost

VOC : Minimal EU values for the product (cat IIA/a) are 75g/l(2007) and 30g/l(2010), current value is 1.8g/l

Remarque : Warranty invalid, if other system than provided by ROBIN S.A. is used

Nota : cancel and replaces the former editions. It's up to our customers to check, before application, if it is indeed the last edition. The information contained in this note has only one indicative range and can not compensate a description suitable with the nature and the state of funds to be treated.