



## JUNGLE KIT ELEPHANT

### Technical Sheet

**NAME:**

**TYPE:**

**CHARACTERISTICS:**

**JUNGLE KIT ELEPHANT**

water-based coating for interior

**specific**

**PRIMER 700:** 1.420 ± 30 gr/LT at 25°C

**weight:**

**EL 630:** 1.700 ± 30 gr/LT at 25°C

**EL 631:** 1.210 ± 30 gr/LT at 25°C

**EL 632 TRASPARENTE:** 1.045 ± 30 gr/LT at 25°C

**yeild:**

3 e 10 m<sup>2</sup> (it may vary according to the roughness, porosity and surface absorption and to the method of application)

**colours:**

colours from the catalogue

**packaging:**

3 and 10 sqm

**DRYING:**

**aesthetic effect:**

1 ora a 20°C

**overpainting:**

3 - 4 hours at 20°C

**below the surface:**

24 hours at 20°C

**CHARACTERISTICIS AND RESISTANCE:**

JUNGLE KIT ELEPHANT comprises a series of liquid and creamy water-based decorative paints for interiors that offer unique visual effects of extraordinary beauty.

After its complete hardening and drying a breathing film forms with a good resistance to bumps and standard 15 days after its application cycle the surfaces achieves its definitive qualities so it become breathable, resistant to washing with water and common neuter detergents.

**PREPARATION OF THE SURFACE:**

JUNGLE Decorative Paints can be applied to various surfaces including cement (new or old), plasterboard, plaster of Paris, wood (new or old), plastic, glass and iron (new or old), provided they are free of humidity, well dry, smooth and have already been treated.

Any loose or dusty paint, as well as any grease or rust, must be removed and the surface washed with suitable soap. Fill the surfaces to be decorated, if necessary, and apply a base coat that is suitable to the type of surface to be treated.

Once the base coat is dry, apply the JUNGLE Range products as indicated in the JUNGLE KIT

**PREPARATION OF THE PRODUCT:**

**dilution:**

all the products in the JUNGLE KIT ELEPHANT are ready to use and must be carefully mixed before and during the application.

**APPLICATION CYCLE:**

**1) PRIMER 700.** (Coverage 0.080 l/sqm) Apply a coat using a wool roller. Allow to dry for 4 hours at 20°C, then proceed to Point 2.

**2) Place the EL 11K STENCILS** over the entire surface to be treated and align the connection points between the various stencils. Proceed to Point 3 once the procedure is completed.

**3) EL 630 already coloured.** (Coverage 0.800 l/sqm) Using the stainless steel trowel, spread a 2-3 mm thick coat of product in the least uniform way painting the final strips with horizontal and slightly striated stokes. Remove the stencils and allow to dry for about 6 hours at 20°C then sand the surface lightly to remove any lumps. Proceed to Point 4.



**SC 00213**

**4) PRIMER 700.** (Coverage 0.100 l/sqm) Apply a coat using the wool roller; allow to dry for 4 hours at 20°C then proceed to Point 5.

**5) EL 631 must be coloured prior to application using COLORI' or the VALCLONE Dispensing System. The shades EL 631/500 - 631/501 - 631/502 cannot be coloured with COLORI' but only using the Paint Dispenser, or directly by VALPAINT.**

(Coverage 0.100 l/sqm) Apply two layers with a brush. Allow the first layer to dry for approx. 1 hour at 20°C before applying the second layer; use a 3 x 10 cm handle-free brush. Wet the bristles up to a maximum of 1-2 mm and apply the product with round strokes only, while adjusting the pressure accordingly to create light-dark nuances. Allow the second coat of EL 631 to dry for approx. 2 hours at 20°C before proceeding to Point 6.

**6) EL 632 TRANSPARENT.** (Coverage 0.200 l/sqm) Apply three layers with a wool roller and wait at least 1 hour before each successive application.

**N.B.:** All the above-mentioned phases must be completed without interruptions once they are started, while any areas that have already been coated must not be retouched

**Stability:** 2 years approximately.

**NOTES:**

Application temperature must be between +5°C and +30°C. Wash the tools soon after use with use.

**Technical Sheet n° SC 00213 issued by the Control Quality Department**

**Edition n° 1**

**April 2009**