



robin

La qualité en peinture

Technical datasheet

RAPIDOLAC

Internal and external covering coat (topcoat lacquer)

Composition: Alkyd-resin, long-oil

Appearance: high gloss finished

Key features and application:

The acrylic resin RAPIDOLAC owns a high coverage. Perfect spreadability, good run and high gloss guarantee quality work.

Can be applied for internal and external use on wood, doors, windows, roll shutters, walls, heaters and ceilings of kitchens, bathrooms, houses and garden furniture made of wood, metal etc.

Instructions for use:

Stir well before usage. Easy to apply with brush, roller or paint sprayer.

Neat colour-coats require a previous filling with Spartol. Dilute with a small amount of test-fuel for the first layer on absorbent surfaces the first layer

Drying:

Dust-dry: 3-4 hours

Paintable after 12 hours

Hard-dry: 24 hours

Cleaning and dilution:

White Spirit or Thinner

Consumption: 10 - 12 m²/Ltr

Colour shades:

RAPIDOLAC is in stock and deliverable in the 50 shades of our ROBIN-colour-card.

The shades of the ROBIN-MIX cards, RAL, DIN, NCS, British Standard etc are available on order.



r o b i n

La qualité en peinture

Package size: 250 ml – 750 ml – 2,5 Ltr – 20 Ltr

VOC : EU limits for this product (Kat. A/d), 400g/l(2007), 300g/l(2010);

Rapidolac contains < 300g/l VOC

If applied on a substrate without daylight the paint can be subject to yellowing. This is a natural reaction of the resin. Robin can not be hold responsible for this

Explanatory note : This product will not be guaranteed anymore if it is tinted by other systems than those of ROBIN S.A.

Note: cancels and replaces former editions. It is up to our customers to check, before application, that this is indeed the last edition. The information contained in this note has only one indicative range and cannot compensate a description suitable with the nature and the state of the funds to be treated.